VISAPP 2012

International Conference on Computer Vision Theory and Applications

Proceedings

Volume 2

Rome, Italy · 24 - 26 February, 2012

Sponsored by:



VISAPP 2012

Proceedings of the International Conference on Computer Vision Theory and Applications

Volume 2

Rome, Italy

24 - 26 February, 2012

Sponsored by INSTICC – Institute for Systems and Technologies of Information, Control and Communication

Copyright © 2012 SciTePress – Science and Technology Publications All rights reserved

Edited by Gabriela Csurka and José Braz

Printed in Portugal ISBN: 978-989-8565-04-4 Depósito Legal: 339063/12

http://www.visapp.visigrapp.org visapp.secretariat@insticc.org

CONTENTS

INVITED SPEAKERS

KEYNOTE SPEAKERS

IMPROVING THE VISIBLE WITH THE INVISIBLE - Incorporating Near-infrared Cues in Computational Photography and Computer Vision Tasks <i>Sabine Süsstrunk</i>	IS-5
VISUAL THINKING ALGORITHMS Colin Ware	IS-7
FIRST-PERSON VISUO-HAPTIC ENVIRONMENT - From Research to Applications Sabine Coquillart	IS-11
LINEAR AND NONLINEAR SHAPE ALIGNMENT WITHOUT CORRESPONDENCES Zoltan Kato	IS-13
APPLICATIONS AND SERVICES	
FULL PAPERS	
FAST BEAD DETECTION AND INEXACT MICROARRAY PATTERN MATCHING FOR IN-SITU ENCODED BEAD-BASED ARRAY Soumita Ghosh, Andreas Schmidt and Dieter Trau	5
A STEREOSCOPIC AUGMENTED REALITY SYSTEM FOR THE VERIDICAL PERCEPTION OF THE 3D SCENE LAYOUT M. Chessa, M. Garibotti, A. Canessa, A. Gibaldi, S. P. Sabatini and F. Solari	15
3D RECONSTRUCTION OF PLANT ROOTS FROM MRI IMAGES Hannes Schulz, Johannes A. Postma, Dagmar van Dusschoten, Hanno Scharr and Sven Behnke	24
SHORT PAPERS	
IMAGE HIDING USING THE DIFFERENCE OF MODIFIED HISTOGRAM AND PREDICTOR Hui-Yu Huang and Shih-Hsu Chang	37
SEGMENTATION OF PLANAR STRUCTURES IN BIOIMAGING A. Martinez-Sanchez, I. Garcia and J. J. Fernandez	42
REAL-TIME FACE SWAPPING IN VIDEO SEQUENCES - Magic Mirror Nuri Murat Arar, Fatma Güney, Nasuh Kaan Bekmezci, Hua Gao and Hazım Kemal Ekenel	48
RELEVANCE FEEDBACK AS AN INTERACTIVE NAVIGATION TOOL Daniele Borghesani, Costantino Grana and Rita Cucchiara	54
3D TEXTURE SYNTHESIS FOR MODELING REALISTIC ORGANIC TISSUES Juan-Carlos Prieto, Chantal Revol-Muller, Françoise Peyrin, Patrizia Camelliti and Christophe Odet	60
TEXTURE OVERLAY ONTO NON-RIGID SURFACE USING COMMODITY DEPTH CAMERA Tomoki Hayashi, Francois de Sorbier and Hideo Saito	66

POSTERS

OPTICALLY WRITTEN WATERMARKING TECHNOLOGY USING ONE DIMENSIONAL HIGH FREQUENCY PATTERN Kazutake Uehira and Mizuho Komori	75
FAST CALIBRATION METHOD FOR ACTIVE CAMERAS Piero Donaggio and Stefano Ghidoni	79
INTEGRITY AUTHENTICATION METHOD FOR JPEG IMAGES USING REVERSIBLE WATERMARKING Hyun-Wu Jo, Dong-Gyu Yeo and Hae-Yeoun Lee	83
CONTENT-BASED IMAGE RESIZING ON MOBILE DEVICES Sebastiano Battiato, Giovanni Maria Farinella, Nicolò Grippaldi and Giovanni Puglisi	87

MOTION, TRACKING AND STEREO VISION

FULL PAPERS

TRACKING-BY-REIDENTIFICATION IN A NON-OVERLAPPING FIELDS OF VIEW CAMERAS NETWORK Boris Meden, Frédéric Lerasle, Patrick Sayd and Christophe Gabard	95
TRACKING INTERACTING OBJECTS IN COMPLEX SITUATIONS BY USING CONTEXTUAL REASONING Rosario Di Lascio, Pasquale Foggia, Alessia Saggese and Mario Vento	104
SELF-CONSISTENT 3D SURFACE RECONSTRUCTION AND REFLECTANCE MODEL ESTIMATION OF METALLIC SURFACES Steffen Herbort and Christian Wöhler	114
FAST PROTOTYPING OF EMBEDDED IMAGE PROCESSING APPLICATION ON HOMOGENOUS SYSTEM - A Parallel Particle Filter Tracking Method on Homogeneous Network of Communicating Processors (HNCP) <i>Hanen Chenini, Jean Pierre Derutin and Thierry Chateau</i>	122
OPTIMAL CONTROL THEORY FOR MULTI-RESOLUTION PROBLEMS IN COMPUTER VISION - Application to Optical-flow Estimation <i>Pascal Zille and Thomas Corpetti</i>	134
A NOVEL STATE PARAMETRIZATION FOR STEREO-SLAM Arne Petersen and Reinhard Koch	144
AN EVALUATION METHODOLOGY FOR STEREO CORRESPONDENCE ALGORITHMS Ivan Cabezas, Maria Trujillo and Margaret Florian	154
MCMC PARTICLE FILTER WITH OVERRELAXATED SLICE SAMPLING FOR ACCURATE RAIL INSPECTION Marcos Nieto, Andoni Cortés, Oihana Otaegui and Iñigo Etxabe	164
OCCLUSION HANDLING FOR THE INTEGRATION OF VIRTUAL OBJECTS INTO VIDEO Kai Cordes, Björn Scheuermann, Bodo Rosenhahn and Jörn Ostermann	173
REAL-TIME POSE ESTIMATION USING TREE STRUCTURES BUILT FROM SKELETONISED VOLUME SEQUENCES Rune Havnung Bakken and Adrian Hilton	181

OBJECT VOLUMETRIC ESTIMATION BASED ON GENERIC FITTED PRIMITIVES FOR SERVICE ROBOTICS *Tiberiu T. Cociaş, Sorin M. Grigorescu and Florin Moldoveanu*

SHORT PAPERS

ENERGY-MINIMIZATION BASED MOTION ESTIMATION USING ADAPTIVE SMOOTHNESS PRIORS <i>Tarik Arici and Vural Aksakalli</i>	201
ENHANCING MEMORY-BASED PARTICLE FILTER WITH DETECTION-BASED MEMORY ACQUISITION FOR ROBUSTNESS UNDER SEVERE OCCLUSION Dan Mikami, Kazuhiro Otsuka, Shiro Kumano and Junji Yamato	208
DENSE PIXEL MATCHING BETWEEN UNRECTIFIED AND DISTORTED IMAGES USING DYNAMIC PROGRAMMING Jerome Thevenon, Jesus Martinez-del-Rincon, Romain Dieny and Jean-Christophe Nebel	216
ACCELERATED PEOPLE TRACKING USING TEXTURE IN A CAMERA NETWORK Wasit Limprasert, Andrew Wallace and Greg Michaelson	225
IMPROVEMENT OF MOTION ESTIMATION BY ASSESSING THE ERRORS ON THE EVOLUTION EQUATION Isabelle Herlin, Dominique Béréziat and Nicolas Mercier	235
BAYESIAN PERSPECTIVE-PLANE (BPP) FOR LOCALIZATION Zhaozheng Hu and Takashi Matsuyama	241
NON-PARAMETRIC ACQUISITION OF NEAR-DIRAC PIXEL CORRESPONDENCES Bradley Atcheson and Wolfgang Heidrich	247
GPU-FRIENDLY MULTI-VIEW STEREO FOR OUTDOOR PLANAR SCENE RECONSTRUCTION Hyojin Kim, Quinn Hunter, Mark Duchaineau, Kenneth Joy and Nelson Max	255
A PATCH RECTIFICATION STRATEGY FOR MULTI-HOMOGRAPHY ESTIMATION <i>Mario Santes</i>	265
PARAMETER AND CONFIGURATION ANALYSIS FOR NON-LINEAR POSE ESTIMATION WITH POINTS AND LINES Martin Schumann, Bernhard Reinert and Stefan Mueller	271
OCCUPANCY ANALYSIS OF SPORTS ARENAS USING THERMAL IMAGING Rikke Gade, Anders Jørgensen and Thomas B. Moeslund	277
HEAD SHAPE ESTIMATION USING A PARTICLE FILTER INCLUDING UNKNOWN STATIC PARAMETERS Catherine Herold, Vincent Despiegel, Stéphane Gentric, Séverine Dubuisson and Isabelle Bloch	284
3D HUMAN BODY POSE ESTIMATION BY SUPERQUADRICS Ilya Afanasyev, Massimo Lunardelli, Nicolò Biasi, Luca Baglivo, Mattia Tavernini, Francesco Setti and Mariolino De Cecco	294
REAL TIME OBJECT TRACKING ON GPGPU Maciej Chociej and Adam Polak	303

191

HIGH RESOLUTION POINT CLOUD GENERATION FROM KINECT AND HD CAMERAS USING GRAPH CUT Suvam Patra, Brojeshwar Bhowmick, Subhashis Banerjee and Prem Kalra	311
SINGLE SNAPSHOT SYSTEM FOR THE FAST 3D MODELING USING DYNAMIC TIME WARPING Luis Ruiz, Xavier Mateo, Ciro Gràcia and Xavier Binefa	317
ANALYSIS OF DEFORMATION PROCESSES USING BLOCK-MATCHING TECHNIQUES Alvaro Rodriguez, Carlos Fernandez-Lozano, Jose-Antonio Seoane, Juan R. Rabuñal and Julian Dorado	327
POSTERS	
SOLVING THE THREE-POINT CAMERA POSE PROBLEM IN THE VICINITY OF THE DANGER CYLINDER Michael Q. Rieck	335
PUTATIVE MATCH ANALYSIS - A Repeatable Alternative to RANSAC for Matching of Aerial Images Anders Hast and Andrea Marchetti	341
SEMI-AUTOMATIC FLOOR-PLAN RECONSTRUCTION FROM A 360° PANORAMIC IMAGE Alexander Tarnavsky, Alexander Yusupov and Dmitry Rudoy	345
A SIMPLE DERIVATION TO IMPLEMENT TRACKING DISTRIBUTIONS Wei Yu, Jifeng Ning, Nan Geng and Jiong Zhang	351
STEREO VISION-BASED 3D CAMERA POSE AND OBJECT STRUCTURE ESTIMATION - An Application to Service Robotics Sorin M. Grigorescu, Tiberiu T. Cociaş, Gigel Maceşanu and Florin Moldoveanu	355
REAL-TIME 3D MULTIPLE HUMAN TRACKING WITH ROBUSTNESS ENHANCEMENT THROUGH MACHINE LEARNING Suraj Nair, Emmanuel Dean-Leon and Alois Knoll	359
FRAME INTERPOLATION WITH OCCLUSION DETECTION USING A TIME COHERENT SEGMENTATION Rida Sadek, Coloma Ballester, Luis Garrido, Enric Meinhardt and Vicent Caselles	367
KERNEL SELECTION BY MUTUAL INFORMATION FOR NONPARAMETRIC OBJECT TRACKING J. M. Berthommé, T. Chateau and M. Dhome	373
FAST STEREO MATCHING METHOD BASED ON OPTIMIZED CORRELATION ALGORITHM FOR FACE DEPTH ESTIMATION Amel Aissaoui, Rémi Auguste, Tarek Yahiaoui, Jean Martinet and Chabane Djeraba	377
VEHICLE SPEED ESTIMATION FROM TWO IMAGES FOR LIDAR SECOND ASSESSMENT Charles Beumier	381
PARAMETRIC DATA ASSOCIATION PRIOR FOR MULTI-TARGET TRACKING BASED ON RAO-BLACKWELLIZED MONTE CARLO DATA ASSOCIATION Oliver Greß and Stefan Posch	387
COMPARISON OF GLOBAL-APPEARANCE TECHNIQUES APPLIED TO VISUAL MAP BUILDING AND LOCALIZATION Francisco Amorós, Luis Payá, Oscar Reinoso and Luis M. Jiménez	395

ADAPTIVE SEARCH-BASED HIERARCHICAL MOTION ESTIMATION USING SPATIAL PRIORS	399
Michael Santoro, Ghassan Al-Regib and Tucel Allundasak	
PEOPLE COUNTING WITH STEREO CAMERAS - Two Template-based Solutions Tim van Oosterhout, Ben Kröse and Gwenn Englebienne	404
COVARIANCE BASED FISH TRACKING IN REAL-LIFE UNDERWATER ENVIRONMENT Concetto Spampinato, Simone Palazzo, Daniela Giordano, Isaak Kavasidis, Fang-Pang Lin and Yun-Te Lin	409
UTILIZATION AND PERFORMANCE CONSIDERATIONS IN RESOURCE OPTIMIZED STEREO MATCHING FOR REAL-TIME RECONFIGURABLE HARDWARE Fredrik Ekstrand, Carl Ahlberg, Mikael Ekström, Lars Asplund and Giacomo Spampinato	415
THE EFFECT OF FEATURE COMPOSITION ON THE LOCALIZATION ACCURACY OF VISUAL SLAM SYSTEMS <i>Mohamed Heshmat and Mohamed Abdellatif</i>	419

AUTHOR INDEX

425

COMPARISON OF GLOBAL-APPEARANCE TECHNIQUES APPLIED TO VISUAL MAP BUILDING AND LOCALIZATION Extracting the Most Relevant Information from Panoramic Images

Francisco Amorós, Luis Payá, Oscar Reinoso and Luis M. Jiménez Departamento de Ingeniería de Sistemas y Automática, Miguel Hernández University, Avda. de la Universidad s/n, 03202, Elche (Alicante), Spain Ipaya@umh.es, o.reinoso@umh.es

Keywords: Robot Mapping, Appearance-based Methods, Omnidirectional Vision, Spatial Localization.

Abstract: Techniques based on the global appearance of visual information have proved to be a robust alternative in the field of robotic mapping and localization. However, they present some critical issues that must be studied when trying to build an application that works in real time. In this paper, we review and compare several methods to build a global descriptor of panoramic scenes and we study the critical parameters that make their applicable or not in real mapping and localizations tasks, such as invariance against rotations, computational costs and accuracy in robot localization. All the experiments have been carried out with omnidirectional images captured in a real environment under realistic lighting conditions.

1 INTRODUCTION

When a robot or a team of robots has to carry out a task that implies autonomous navigation through an environment, an internal representation of this environment is needed. This representation has to allow the robot to estimate its position and orientation using the information provided by the sensors it is equipped with. Omnidirectional visual systems are commonly used with this goal due to the richness of the information they provide and the relatively low cost they have. Classical researches into mobile robots provided with vision systems have focused on local features descriptors, extracting natural or artificial landmarks from the image to build the map and carry out the localization of the robot (Thrun, 2003).

Recent approaches propose processing the image as a whole without local feature extraction. These appearance-based techniques are interesting when dealing with unstructured environments where it may be hard to find patterns to recognize the scene. But we have to work with a large amount of information, having a high computational cost. That is the reason why we need to study compression techniques.

The localization task requires techniques that present rotational invariance in order to recognise the most similar image regardless of the robot's orientation in the ground plane. But some orientation information to estimate the pose of the robot is also necessary. Incremental methods are also advisable, since some navigation tasks require to add or modify elements of the map as the robot moves through the environment.

Several approaches to compress the visual information can be found in the literature. For example, PCA (Principal Components Analysis) has demonstrated being robust applied to image processing, as (Krose et al., 2007) shows. Other authors use the Fourier Transform to extract the most relevant information of an image (Menegatti et al., 2004).

(Paya et al., 2009) present a comparative study about appearance-based techniques. We complement this study and take into account three methods: Fourier Signature, Rotational PCA and Gist-Gabor. The last technique has proved previous promising results, although we have no notice it has been previously used in localization and mapping tasks.

2 REVIEW OF COMPRESSION TECHNIQUES

In this section we summarize some techniques to extract the most relevant information from a database made up of panoramic images.

2.1 Fourier-based Techniques

As shown in (Menegatti et al., 2004) it is possible to represent an image using the Discrete Fourier Transform of each row. Taking profit of the Fourier Transform properties, since the most relevant information concentrates in the low frequency components of the sequence, we keep the first coefficients to represent each row. Moreover, as we work with omnidirectional images, when the Fourier Transform of each row is computed, another interesting property appears: rotational invariance. Comparing the transform of a row and the transform of the same sequence rotated, the modulus are the same and just the phase changes. The modulus let the position estimation, and with the phase coefficients we can find out the relative rotation.

2.2 PCA-based Techniques

PCA-based techniques have proved to be a very useful compressing method (Krose et al., 2007). They make possible that, having a set of N images with M pixels each, $\vec{I}^j \in \Re^{M_{x1}}, j = 1...N$, we could transform each image in a feature vector (also named projection of the image $\vec{p}^j \in \Re^{kx1}, j = 1...N$, being k the PCA features containing the most relevant information of the image, $k \leq N$. However, if we apply PCA directly over the matrix that contains the images, we obtain a database with information of just one orientation of each scene. To solve this problem, in (Leonardis and Jogan, 2000) the use of the Eigenspace of Spining-Images is proposed. This technique creates a set of spinning images from every image included in the map. After that, the database is compressed by means of PCA analysis. The robustness in localization and angular resolution of the map depends on the number of rotated siblings of each image we include.

2.3 Gist-based Techniques

Gist is another concept that can be used to compress visual information as (Friedman, 1979) details. It can be defined as an abstract representation that activates the memory of scenes' categories. They try to obtain the essential information of the image simulating the human perception system, i.e., identifying a scene through its colour or remarkable structures, avoiding the representation of specific objects. In (Oliva and Torralba, 2001) this idea is developed under the name of *holistic representation of the spatial envelope* to create a descriptor. In (Torralba, 2003) this model is computed using global scene features, such as spatial frequencies and different scales based on Gabor filtering. Although it has demonstrated its capacity for scene recognition and classification, we have not found any reference of applications in robotic mapping and localization tests. The descriptor we propose is named Gist-Gabor since it uses Gabor filtering in order to obtain frequency and orientation information using the global image.

The first step consists in creating a bank of the Gabor masks with different resolutions and orientations. Then, the image is filtered with the set of filters. The results encode different structural information. To create the descriptor, we calculate the average pixel's value within cells with the same width as the omnidirectional image, obtaining an array of rotational invariant characteristics. To know the relative orientation between two rotated images, vertical windows with the image's height are used, making up a vector with the mean value the pixels they contains. By rotating the order of its components and comparing with the database we estimate the orientation.

3 LOCALIZATION AND ORIENTATION RECOVERING

In this section we assess each algorithm by calculating the pose of the robot within a map created previously, and the time they spent. The image database we have used to carry out the experiments belongs to the Technique Faculty of Bielefeld University ((Moeller et al., 2007). It has been collected in three different living spaces under realistic illumination conditions. The images are structured in a 10x10 cm rectangular grid. In the experiments, we have varied the distance between images of the database when building the map to simulate different conditions. Table 1 shows the different grids information.

Table 1: Grid's size and number of images selected.

	GridA	GridB	GridC	GridD
Distance	10cm	20cm	30cm	40cm
Images	746	204	92	54

The test set is made up of all the available images in the database and 15 artificial rotations of each one (every 22.5°), but the images included in the map. The simulations have been obtained using Matlab R2009b under Mac OS X. The position retrieval accuracy is studied as binary results, considering if we obtain the best match as possible or not, and the information is showed with recall and precision measurement (Gil et al., 2009), with information about if a correct location is in the Nearest Neighbour (N.N.), i. e., if it is the first result selected, or between Second or Third Nearest Neighbours (S.N.N or T.N.N).



Figure 1: Elapsed time for (a) location and (b) pose estimation using Fourier-based algorithm. Elapsed time for (c) location and (d) pose estimation using PCA-based algorithm. Elapsed time for (e) location and (f) pose estimation using Gist-Gabor. Recall-Precision charts using grid D for (g) Fourier-based algorithm, (h) PCA-based algorithm and (i) Gist-Gabor. Phase error over correct locations using Grid D for (j) Fourier-based algorithm, (k) PCA-based algorithm and (l) Gist-Gabor.

Regarding the rotation, we represent the results accuracy in bar graphs depending on how much they differ from the correct ones, in percentage over correct locations. In order to avoid redundant information, we include only the pose estimation experiments in the most critical case, i.e., using the Grid D.

3.1 Fourier Signature Technique

The map obtained with the Fourier Signature is represented with two matrices: the module and the phase of the selected Fourier Coefficients. The location is estimated by calculating the minimum Euclidean distance of the power spectrum between the image and the spectra of the map. The phases' vector associated with the most similar image retrieved in the map is used to compute the orientation. In fig.1(a) we can see that, to find the position, the elapsed time rises in accordance with the number of images the map stores, i.e. the grid, and the number of Fourier components. But the pose depends almost only on the number of coefficients per row (fig.1(b)). This is due to the orientation estimation, since it is the computationally heaviest part of the algorithm and it depends only on the number of components we use. Regarding the position recovering, fig.1(g) show that in both experiments the algorithm is able to find the best match using a relatively low number of Fourier components. The phase lag appears in fig.1 (j). The algorithm is able to recover the orientation using 10 components with an error less than or equal 5 degrees in the 92 per cent of correct locations.

3.2 PCA-based Techniques

When a new image $\vec{I} \in \Re^{1xM}$ arrives, it is projected onto the eigenspace $\vec{p} = V^T \cdot \vec{I} \in \Re^{kx1}$. The location is estimated by computing the module of \vec{p} and comparing with the modules of the projections of the map. The criterion is the minimum Euclidean distance. Once the position is known, we use the phases vector \vec{p}_{ph} to simulate the projections of the rotated siblings of the image to determine the orientation. Fig. 1(c) and (d) show the time spent on location and pose estimation. Comparing both charts we can see that, except in Grid A, the measurements are similar, demonstrating that the phase recovering is quite fast. Even so, this algorithm is the slowest in the majority of the experiments. Fig.1(h) shows that with 16 rotations and 100 eigenvectors the position estimation presents good accuracy. Fig.1(k)) shows that, with 16 rotations, the percentage of experiments equal than or under one degree is 86% although in the rest of the experiments is greater than 10 degrees.

3.3 Gist-based Techniques

To extract the information of a test image, we filter the image with the same Gabor masks used to built the map. The maximum number of spatial escales used is two. After that, we compute the descriptor using the same horizontal and vertical cells as in the map. The elapsed time in the position recovering (fig. 1(e)) depends on the number of Gabor masks we use in order to filter the image. Fig. 1(f) shows the relationship between the elapsed time in pose estimation and the orientation parameters. The number of vertical cells determines the results over its size. The position estimation presents good accuracy with few masks (fig. 1(i)). The phase retrieval results appear in fig.1(1). The descriptor is able to estimate the orientation of almost all the experiments without error using 16 vertical cells. But they are binary results, since the angle is discretized depending on the number of vertical cells we apply to the image.

4 CONCLUSIONS

In this paper we have presented the comparison of different appearance-based algorithms applied to the creation of a descriptor using panoramic images. We have studied the elapsed and the accuracy in the pose estimation regarding a previously created map.

All of them have demonstrated to be perfectly valid to carry out the estimation of the pose of a robot within the map. However, when the number of images included in the map grows, the computational cost of PCA descriptor can make it application unfeasible. Moreover, it is a non-incremental method.

Regarding the elapsed time, rotational PCA exceeds the other methods. Gist-Gabor lasts longer than Fourier Signature, and it is more dependant on the quantity of information it stores, i.e. the number of masks we use to filter the image. The three algorithms present a high rate of retrieved positions, being Fourier Signature remarkable.

In the orientation estimation task, PCA technique has the lowest accuracy. Although Gist-Gabor outperforms Fourier Signature, Gist-Gabor angle's estimation is sampled with regard to the number of cells we use, and it could increase time and memory consumptions as we need higher accuracy.

To finish, this paper proves again the possibilities that appearance-based techniques offer. The results achieved encourage us to continue studying new possibilities and deepening in its development, looking for new available techniques and improving its robustness to illumination change, noise or occlusions.

ACKNOWLEDGEMENTS

This work has been supported by the Spanish government through the project DPI2010-15308.

REFERENCES

- Friedman, A. (1979). Framing pictures: The role of knowledge in automatized encoding and memory for gist. In *Journal of Experimental Psychology: General*, 108:316-355.
- Gil, A., Martinez, O., Ballesta, M., and Reinoso, O. (2009). A comparative evaluation of interest point detectors and local descriptors for visual slam. SPRINGER Machine Vision and Applications.
- Krose, B., Bunschoten, R., Hagen, S., Terwijn, B., and Vlassis, N. (2007). Visual homing in environments with anisotropic landmark distrubution. In *Autonomous Robots*, 23(3), 2007, pp. 231-245.
- Leonardis, A. and Jogan, M. (2000). Robust localization using eigenspace of spinning-images. In *IEEE Work-shop Omnidirectional Vision*. Proceedings of the IEEE Workshop on Omnidirectional Vision, IEEE Computer Society,pp. 37-44.
- Menegatti, E., Maeda, T., and Ishiguro, H. (2004). Imagebased memory for robot navigation using properties of omnidirectional images. In *Robotics and Autonomous Systems. Vol.* 47, No. 4, pp. 251-276.
- Moeller, R., Vardy, A., Kreft, S., and Ruwisch, S. (2007). Visual homing in environments with anisotropic landmark distrubution. In *Autonomous Robots*, 23(3), 2007, pp. 231-245.
- Oliva, A. and Torralba, A. (2001). Modeling the shape of the scene: a holistic representation of the spatial envelope. In *International Journal of Computer Vision*, *Vol.* 42(3): 145-175.
- Paya, L., Fenandez, L., Reinoso, O., Gil, A., and Ubeda, D. (2009). Appearance-based dense maps creation: Comparison of compression techniques with panoramic images. In 6th Int Conf on Informatics in Control, Automation and Robotics. Ed. INSTICC PRESS ISBN: 978-989-674-000-9 - pp.250-255.
- Thrun, S. (2003). Robotic mapping: A survey, in exploring artificial intelligence. In *The New Milenium*, pp. 1-35. Morgan Kaufmann Publishers, San Francisco, USA.
- Torralba, A. (2003). Contextual priming for object detection. In International Journal of Computer Vision, Vol. 53(2), 169-191.